



InDesign-Skripting-Kurzreferenz

© Creative Commons BY-NC-SA 3.0

- PageItem Klasse
- .pageItems Sammlung
- .name Eigenschaft
- LinkStatus Aufzählung/Enumeration
- Page .move(LocationOptions, Page) Methode mit Parameter und Rückgabewert
- Sammlung zu Klasse
- Eigenschaft zu Klasse
- Klasse zu Basisklasse
- readonly
- ↔ read/write
- # Zahl/Number

- .geometricBounds ↔ [y1,x1,y2,x2]
- .visibleBounds ↔ [y1,x1,y2,x2]
- .fillColor ↔ Swatch
- .textWrapPreferences → TextWrapPreference
- .appliedObjectStyle
- .strokeWeight ↔ #
- .strokeColor ↔ Swatch
- .overridden → bool
- .parentPage (CSS) → Page
- [any] .place(File)
- .applyObjectStyle(ObjectStyle)
- .fit(FitOptions)
- any .override(Page)

Sammlungen

- [index]
- .length → #
- Object itemByName(Name)
- Object itemByID(ID)
- [Object] everyItem()
- [Object] itemByRange(from, to)
- Object add()

Document

- .viewPreferences → ViewPreference
- .zeroPoint ↔ [x,y]
- .name → String
- .fullName → File
- .links ↔
- .masterSpreads
- .spreads
- .pages
- .pageItems ↔
- .objectStyles ↔
- .allGraphics → [Graphics]
- .stories
- .paragraphStyles ↔
- .characterStyles ↔
- .tableStyles ↔
- .cellStyles ↔
- .swatches
- .tints
- .colors
- [Text] .findGrep()
- [Text] .changeGrep()
- .close(SaveOptions)
- .exportFile(ExportFormat, File)

MasterSpread

- .namePrefix ↔ String
- .baseName ↔ String
- .pageItems ↔
- .pages

Spread

- .pages

Page

- .appliedMaster
- .name → String
- .masterPageItems
- .pageItems
- .groups
- .rectangles
- .textFrames
- .side → PageSideOptions
- Page .move(LocationOptions, Page)
- .remove()

PageItem

Group

TextFrame

- .parentStory
- .nextTextFrame ↔ TextFrame
- .previousTextFrame ↔ TextFrame
- .paragraphs ↔
- .insertionPoints ↔
- .lines ↔
- .characters ↔
- .textStyleRanges ↔
- .textFramePreferences → TextFramePreference
- [Text] .findGrep()
- [Text] .changeGrep()

Rectangle

- .textWrapPreferences → TextWrapPreference
- .pdfs
- .graphics
- .images

Graphics

- .geometricBounds ↔ [y1,x1,y2,x2]
- .itemLink

Image

- .actualPpi → [h,v]
- .effectivePpi → [h,v]

Link

- .name → String
- .filePath → String
- .status → LinkStatus
- .relink(File)
- Link .update()

Story

- .textContainers
- .paragraphs
- .textStyleRanges
- .insertionPoints
- .lines
- .characters
- [Text] .findGrep()
- [Text] .changeGrep()

Paragraph

TextStyleRange

InsertionPoint

Character

Line

Text

- .parentTextFrames → TextFrame
- .parentStory → Story
- .contents ↔ String
- .appliedParagraphStyle → ParagraphStyle
- .appliedCharacterStyle → CharacterStyle
- .styleOverridden → bool
- .appliedFont ↔ Font
- .justification ↔ Justification
- .fillColor ↔ Swatch
- .tables
- .pageItems ↔
- .footnotes
- [Text] .findGrep()
- [Text] .changeGrep()
- Text .move(LocationOptions, Text)
- .applyCharacterStyle(CharacterStyle)
- .applyParagraphStyle(ParagraphStyle)

ParagraphStyle

CharacterStyle

Table

- .appliedTableStyle
- .bodyRowCount ↔ #
- .columnCount ↔ #
- .footerRowCount ↔ #
- .headerRowCount ↔ #
- .rows
- .columns
- .cells
- .storyOffset → InsertionPoint

Row

Column

Cell

- .appliedCellStyle
- .parentColumn → Column
- .parentRow → Row
- .texts ...

Footnote

- .storyOffset → InsertionPoint
- .texts ...

app

- .documents
- .activeDocument
- .books
- .activeBook
- .selection ↔ [Object]
- .findGrepPreferences
- .changeGrepPreferences
- .findChangeGrepOptions → FindChangeGrepOption
- .scriptPreferences
- .wordRTFImportPreferences → WordRTFImportPreference
- .fonts
- any .open(File)
- .loadFindChangeQuery(Name, SearchModes)
- .select(Object)
- .doScript(File|Function)

Book

- .bookContents → BookContent

Font

- .fontFamily → String
- .fontName → String
- .status → FontStatus

ScriptPreference

- .version ↔ #
- .userInteractionLevel ↔ UserInteractionLevels

FindGrepPreference

- .findWhat ↔ String (Regular Expression)
- .appliedParagraphStyle ↔ ParagraphStyle
- .appliedCharacterStyle ↔ CharacterStyle

ChangeGrepPreference

- .changeTo ↔ String (Regular Expression)
- .appliedParagraphStyle ↔ ParagraphStyle
- .appliedCharacterStyle ↔ CharacterStyle

Array

- [index]
- .length → #
- length push(Object)
- Object pop()
- Array concat(Array)
- sort(Function)
- String .join(Delimiter)

String

- .length
- # indexOf(String)
- String substring(from, to)
- Array split(Delimiter)

Folder

- .fullName → String
- .desktop → Folder
- Folder .selectDialog(Prompt)
- bool .create()

File

- .name → String
- .fullName → String
- .exists → bool
- .parent → Folder
- bool copy(File)
- bool execute()
- File .openDialog(Prompt)
- File .saveDialog(Prompt)